

Specifications

Tuner/Amplifier Section

Amplifier

Output Power (IEC 268-3/DIN)

30 watts per channel, min. RMS, both channels driven, into 8 ohms at 1 kHz with no more than 0.9% total harmonic distortion.

Input Sensitivity/Impedance (1 kHz)

PHONO 3 mV/47 kohms
AUX/VIDEO 300mV/47 kohms
MIC 2 mV/10 kohms

Speaker terminals

Speakers 8 ohms

Tuner

FM Tuner

Tuning Range 87.5 ~ 108.0 MHz
Usable Sensitivity 0.95 μ V/75 ohms (10.8 dBf)
Signal-to-Noise Ratio (IHF-A weighted) MONO (at 85 dBf) 80 dB
STEREO (at 85 dBf) 73 dB
(DIN) MONO 72 dB
STEREO 64 dB

AM (MW/LW) Tuner

MW-Tuning Range 522 ~ 1,629 kHz
LW-Tuning Range 144 ~ 353 kHz (only for the U.K.)

Dimensions (Approx.) 245 x 183 x 342.5 mm (w/h/d)
(9³/₄ x 7¹/₄ x 13¹/₂ in.)

Weight (Approx.) 4.5 kg (9.9 lbs)

CD/Tape Deck Section

Tape deck

Frequency response

CrO₂: 30 ~ 16,000 Hz

Normal: 30 ~ 15,000 Hz

Wow and Flutter 0.09% (WRMS)/0.2% (DIN)

Compact Disc Player

Dynamic Range (1 kHz) 96 dB

Signal-to-Noise Ratio 102 dB

Wow and Flutter Unmeasurable

Dimensions (Approx.) 245 x 183 x 295 mm (w/h/d)
(9³/₄ x 7¹/₄ x 11⁵/₈ in.)
(Maximum depth 394 mm (15⁹/₁₆ in.)
with the CD tray open)

Weight (Approx.) 4.2 kg (9.3 lbs)

Power specifications

Power Requirements AC 240 V \sim , 50 Hz

Power Consumption 215 Watts

Supplied Accessories

FM feeder antenna (1)

AM loop antenna (1)

Remote control (RM-SEMXS4U) (1)

Batteries R03(UM-4)/AAA(24F) (2)

Antenna adaptor (1)

Design and specifications subject to change without notice.